



PURE M-28W-930-18D 18° |Height, Emax (cm) Ø33 1m 19185lx Ø66 2m 4796lx 3m 2132lx Ø132 4m 1199lx Ø165 5m

PUM1-9301828F-BB

Tracklight round made of die-cast aluminium with black powdercoating finish (RAL 9005) and black reflector, LED 25W, measurement Ø90mm, tracklights length 200mm, luminaires weight is approximately 1140g, rotation 355° and pivot max. 90°, CCT 3000K with an LED Output of 3400lm, with ON-OFF Driver, high color rendering at an index of CRI90, after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips, 5 years warranty, beam characteristic with 18° beam angle, lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19), degree of housing protection according to DIN EN 60529 (IP20)

Designer Neko Neko **Electrical Characteristics** Type Tracklight IP 20

Material	Photometric Data
die-cast aluminium	Beam Angle: 18°

Beam Angle: 18° W

36V

28W W

Downloads

▶ Instructions

Photometry

Dimension

Brand

Light Temperature Colour/Finish 3000K powder-coated

0-90

200