



TL1-9401825D-BW     Brand     Designer       Neko     Neko       Round recessed mounted     Downlight made of die-cast     Type     Electrical Che       aluminium with black powder-     Coiling     IP 54       coating finish (RAL 9005) and white     Ceiling     IP 54       reflector, DALI Dim Driver, LED     26W, measurement Ø218mm,     Acv       narrow mounting trim with a cutout     of Ø200mm, luminaires weight is     Acv       approximately 1700g, CCT 40000K     Material     Photometric I       with an LED Output of 3400lm,     Migh color rendering at an index of     Gie-cast aluminium     Beam Angle:       CRI90, after a lifetime of 50000h     min. 80% of the luminous flux with     Beam Angle:     90       min. 80% of the luminous flux with     Beam Angle:     90       protection according to DIN EN     60529 (IP54)     Dimension	
Round recessed mounted Downlight made of die-cast aluminium with black powder- coating finish (RAL 9005) and white reflector, DALI Dim Driver, LED 25W, measurement Ø218mm, narrow mounting trim with a cutout of Ø200mn, luminaires weight is approximately 1700g, CCT 4000K with an LED Output of 3400lm, high color rendering at an index of CRI90, after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Drips, 5 years warranty, precise beam characteristic with 18° beam angle, degree of housing protection according to DIN EN do329 (IP54)TuestonImensionDownloadsDimensionDownloadsDimensionDownloadsDimension	
Downlight made of die-cast aluminium with black powder- coating finish (RAL 9005) and white reflector, DALI Dim Driver, LED 25W, measurement Ø218mm, narrow mounting trim with a cutout of Ø200mm, luminaires weight is approximately 1700g, CCT 4000K with an LED Output of 3400lm, high color rendering at an index of CRI90, after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips, 5 years warranty, precise beam characteristic with 18° beam angle, degree of housing protection according to DIN EN 60529 (IP54)TypeElectrical Cha 36V 28W WDownloadsMaterialPhotometric I 90	
reflector, DALI Dim Driver, LED 36V 25W, measurement Ø218mm, 28W W narrow mounting trim with a cutout of Ø200mm, luminaires weight is approximately 1700g, CCT 4000K with an LED Output of 3400lm, high color rendering at an index of CRI90, after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips, 5 years warranty, precise beam characteristic with 18° beam angle, degree of housing protection according to DIN EN 60529 (IP54) Downloads Dimension	aracteristics
with an LED Output of 3400lm, high color rendering at an index of CRI90, after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips, 5 years warranty, precise beam characteristic with 18° beam angle, degree of housing protection according to DIN EN 60529 (IP54)Historian Beam Angle: 90DownloadsDimension	
high color rendering at an index of CRI90, after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips, 5 years warranty, precise beam characteristic with 18° beam angle, degree of housing protection according to DIN EN 60529 (IP54)Beam Angle: 90DownloadsDimension	Data
	18° W
▷ Instructions Light Temperature Colour/Finish	
	'n
ht.Emax D Photometry 4000K powder-coate	ed
16424lx	

